



MISSIONSKATALOG · CB-000039

AGT-HTVC6511-2132 WÄRMEBILD-SICHERHEITSKAMERA MIT GROSSER REICHWEITE UND BEWEGUNGSERKENNUNG

**Präzise Langstrecken-Überwachung bei Tag
und Nacht – mit dualspektraler
Wärmebildtechnik.**

Modell AGT-HTVC6511-2132

WICHTIGSTE VORTEILE

- 24-stündige Überwachung über große Distanzen
- Feine und flüssige Bilder
- Einfache Installation und Anwendung
- 360° omnidirektionale Schwenk-/Neigekopf
- Hochfestes Aluminiumgehäuse mit IP66
- Höhere Empfindlichkeit
- In allen Umgebungen effektiv

Angeboten & unterstützt von Circuitbull® (Volls Global Inc.)

- Kompakte Bauweise und geringes Gewicht

BESCHREIBUNG

Die AGT-HTVC6511-2132 ist eine dualspektrale Wärmebild-Sicherheitskamera mit großer Reichweite, die auf einem ungekühlten UFPA-VOx-Detektor der 5. Generation mit 640×512 Auflösung (optional 384×288) und einem 25–105 mm kontinuierlichen Wärmebild-Zoom basiert. Sie ermöglicht die Fahrzeugerkennung bis zu 8,6 km und die Personenerkennung bis zu 3,4 km bei einer NETD von 50 mK @25°C F1.0. Der integrierte Sichtkanal verwendet einen 2-MP-Starlight-CMOS-Sensor mit einem 8–320 mm motorisierten Objektiv, während ein optionaler 8W-810nm-Laser-Illuminator die Nachtleistung erweitert. Die Kamera ist auf einer PTZ mit 50 kg Traglast, 360° Schwenken, ±45° Neigen und 255 Voreinstellungen montiert und unterstützt automatische Rundfahrten, Linienabtastung und Speicherung der Position vor Abschaltung. Intelligente Funktionen umfassen Bereichs-/Grenzüberschreitungs-Erkennung, Zielverfolgung, Feuererkennung, 3D-Rahmenauswahl-Zoom/Positionierung, Panorama-Stitching und Radarverknüpfung. Im integralen Aluminiumgehäuse mit IP66-Schutz (optional IP67) arbeitet sie von -25°C bis +60°C und bietet Überspannungs-, Vibrations- und Salznebelbeständigkeit für raue Außenbereiche.

ÜBERBLICK

- Ungekühlter VOx-Detektor 640×512
- NETD kleiner als 50 mK (@25°C F1.0)
- SDE digitale Bildverarbeitung, AGC, 2X digitale Verstärkung
- 10 Pseudo-Farben sowie Schwarz/Weiß und invertiertes Schwarz/Weiß
- Intelligente Funktionen: Grenzüberschreitungs-/Bereichseinbruchserkennung und Zielverfolgung
- 255 Alarmstufen können eingestellt werden
- Fortschrittlicher Algorithmus unterstützt Schuss-/Feuererkennung und Alarm
- Einteiliges Aluminiumgehäuse, wasserdicht, IP66 wetterfest, staubdicht

ANWENDUNGEN

- Überwachung von Seehäfen und Flughäfen
- Überwachung von Wassersystemen
- Lagerüberwachung
- Sicherheit von Ölfeldern und Öllagern
- Ökologische und Umweltüberwachung
- Grenz- und Küstenverteidigung
- Überwachung von Autobahnen und Eisenbahnen

TECHNISCHE DATEN

THERMAL	
Field of View	30°* 23°~6.2°*4.6°
Zoom	Electric zoom
Focus	manual / auto focus, 3A adaptive active focus algorithm, support multiple trigger modes, precise high speed
Optical Machine	3CAM mode and AS+DOE optical machine structure, high infrared transmittance, no virtual focus and small axis in the zoom process
Image Enhancement	SDE digital image enhancement technology to enhance image details
Pseudo-color / Polarity	16 kinds of pseudo-color images, hot black / hot white two polarities
Image Parameters	AGC automatic gain control, brightness, contrast
Electronic Zoom	2X, 4X, support global synchronous display
NUC Correction	automatic / manual correction, background correction
VISIBLE	
Sensor Type	1/2.8" target surface star-level CMOS, integrated ICR dual filter day and night switching
Resolution	2 Mega pixels, 1920X1080
Min Illumination (Color)	0.05 Lux
Min Illumination (B/W)	0.01 Lux
Encoding	H.265/H.264 video format, support multi-stream
Video Bit Rate	32Kbps ~ 16Mbps
Frame Rate	60Hz 30 frames / sec
Local Storage	SD card local storage
Motion Detection	support

TECHNISCHE DATEN

VISIBLE	
Occlusion Alarm	support
Cross-border Detection	support
Regional Intrusion Detection	support
White Balance	support
Electronic Shutter	support
Strong Light Suppression	support
3D Digital Noise Reduction	support
Wide Dynamic	support
Anti-infrared Over Exposure	support
Lens Focal Length	8 ~ 320mm, 2 Mega pixel high-definition power zoom
Lens Focus	manual / auto focus, 3A adaptive active focus algorithm, support multiple trigger modes, precise high speed
Aperture	Automatic
Day/Night Type Light	0.4-0.75um visible light wide spectral window and 0.8-0.95um near infrared laser narrow spectrum window day and night independent double pass light window to improve imaging light and stray light signal to noise ratio
Preset Position	precision potentiometer, zoom focus feedback
LASER	
Availability	optional
Power	8W
Wavelength	810nm infrared laser
Illumination Angle	1°~ 20°, DSS digital step lighting angle control technology

TECHNISCHE DATEN

LASER	
Homogenization	GHT-II high-definition lens group ultra-homogenization patented technology, brightness balance of all focal lengths is >92%
Laser Safety	ZQB safety laser beam processing patent technology, in line with international IEC60825 safety standards
HOUSING	
Material	integral aluminum alloy housing, stainless steel, anti strong wind
Structure	Integral double window
Window Glass	4mm optical glass, transmission>98%
Surface Coating	PTA three-proofing coatings
IP Rating	IP66 (IP67 optional)
Thermal Balance Design	applied thermal balance design and wide temperature electronics, which could operate under high / low temperature
Connector	waterproof aviation connector
PTZ	
Load	50kg
Pan Range	0 ~ 360°
Tilt Range	-45°~ +45°
Horizontal Speed	0.01°/S ~ 30°/S
Pitch Speed	0.01°/S ~ 15°/S
Speed Adaptive	support lens focal length speed adaptive function
Preset Positions	255, support lens zoom, focus preset
Accuracy	±0.1°
Patrol Sweep	support 6 cruises, 1 apple peel, 1 line sweep

TECHNISCHE DATEN

PTZ	
Watch	Preset / Auto Cruise Route / Auto Scan Route
Power-off Memory	support (recoverable position before power-off, preset position status, cruise status, line sweep status)
Bearing Information	support angle query return, positioning
Zero Point Correction	support north direction zero point remote correction function
Power Consumption	about 100W
Weight	15kg
INTERFACE	
Network Interface	1 way RJ45, 10/100 Base-T adaptive (integrated video output and RS422/485 control communication)
Network Protocol	support TCP/IP, UDP, IPv4/v6; support HTTP, RTP, RTSP, NFS, DHCP, NTP, SMTP, SNMPv1/v2c/v3, UPNP, PPPoE, DNS, FTP; support PSIA, ONVIF2.0, GB28181 and other network protocols
Physical Interface	alloy waterproof aviation plug
POWER	
Power Supply	AC/DC24V, anti-reverse protection
Total Power Consumption	150W
WEIGHT	
Total Weight	35kg (including Pan/Tilt)
ENVIRONMENT	
Working Temperature	-25°C~ +60°C (optional -40°C)
Storage Temperature	-45°C~ +70°C
Humidity	<90%
Earthquake Resistance	0.2g (according to the 5.4 severity level 2 of GB/T15211-2013)
Impact Resistance	15g (according to the 5.3 severe level 3 of GB/T15211-2013)
Lightning Protection	built-in surge protection of interface circuit, power supply 4000V, signal 2000V

TECHNISCHE DATEN

ENVIRONMENT	
Anti-salt Fog	at pH 6.5 ~ 7.2, continuous spraying for 96 hours, no change in surface
ENHANCEMENTS	
Glare Protection	support, anti-sun burn function
Temperature Correction	no thermal image design, imaging resolution is not affected by temperature
Scene Mode	support multiple configuration scenarios, adapt to various environment applications
Auto Focus Tuning	support remote auto focus precision parameter adjustment, adapt to different scenes
Day/Night Cruise	day and night group cruise different preset groups, day cruise 1-40 preset position, night cruise 41-80 preset position, automatically switch day and night according to the photosensitive state, adapt to different time and space scenes
Lens Servo	support lens preset position, focal length return, focus positioning function
OSD Menu	OSD menu remote call operation
Remote Maintenance	support embedded program remote upgrade for easy after-sales maintenance
Alarm Threshold	255 level alarm threshold can be setup
Fire Detection	support shot-point / fire detection and alert
OPTIONS	
Wiper	optional built-in wiper
Window Cleaning	optional external small spray device, self-storing water, no damage to ice, no impact on host function
Expansion Module	optional Beidou / GPS, laser ranging and other extended functions
Optical Network	optional built-in fiber module, single-mode fiber output, improve anti-interference
INTELLIGENT FUNCTIONS	
Regional Intrusion Detection	support
Cross-border Intrusion Detection	support
Multi-scene Group Cruise Detection	support

TECHNISCHE DATEN

INTELLIGENT FUNCTIONS

3D Frame Selection Zoom / Positioning	support
Automatic Tracking	support
Panoramic Stitching	support
Radar Linkage	support (requires key area prevention software)

DOKUMENTENKONTROLLBLATT

HERAUSGEBENDE STELLE	
ORGANISATION	Volls Global Inc
EINGETRAGENER SITZ	1207 Delaware Ave #5352
ORT	Wilmington, DE 19806
LAND	Vereinigte Staaten
ANSPRECHSTELLE	info@circuitbull.com
MARKE	Circuitbull®
DACHORGANISATION	Volls Global · volls.us

MATRIXCODES · ZUM ÖFFNEN SCANNEN			
01	02	03	04
			
DIESES PRODUKT circuitbull.com/.../ agt-hmvc6511-2132-49262612	EINGETRAGENE ANSCHRIFT 1207 Delaware Ave #5352	HAUPTWEBSITE circuitbull.com	VOLLS GLOBAL volls.us

VERTEILUNGSVERMERK
Nach dem Druck unkontrolliert. Prüfen Sie vor Beschaffung oder Verwendung die aktuelle Revision unter der Produktadresse. Dieses Blatt nennt die herausgebende Stelle und die digitalen Adressen dieses Dokuments.