



CATÁLOGO DE MISIÓN · CB-000039

AGT-HTVC6511-2132 CÁMARA DE SEGURIDAD TÉRMICA DE LARGO ALCANCE CON DETECCIÓN DE MOVIMIENTO

Vigilancia térmica de largo alcance con detección inteligente, las 24 horas del día.

Modelo AGT-HTVC6511-2132

BENEFICIOS CLAVE

- Vigilancia las 24 horas de largo alcance
- Imágenes nítidas y fluidas
- Conveniente para instalación y aplicación
- Pan-tilt omnidireccional de 360 grados
- Aleación de aluminio súper resistente con IP66
- Mayor sensibilidad
- Eficaz en todos los entornos
- Tamaño reducido y bajo peso

DESCRIPCIÓN

La AGT-HTVC6511-2132 es una cámara de seguridad térmica de doble espectro y largo alcance construida alrededor de un detector UFPA VOx no refrigerado de quinta generación con resolución de 640×512 (384×288 opcional) y una lente térmica de zoom continuo de 25–105mm. Ofrece detección de vehículos hasta 8,6 km y detección de humanos hasta 3,4 km, con un NETD de 50 mK @25°C F1.0. El canal visible integrado utiliza un sensor CMOS starlight de 2 MP con una lente motorizada de 8–320mm, mientras que un iluminador láser opcional de 8W 810nm extiende el rendimiento nocturno. La cámara está montada en una PTZ con capacidad de 50kg, paneo de 360°, inclinación de $\pm 45^\circ$ y 255 preposiciones, con soporte para crucero automático, escaneo de línea y memoria ante corte de energía. Las funciones inteligentes incluyen detección de intrusión regional/transfronteriza, seguimiento de objetivos, detección de incendios, zoom/posicionamiento por selección de marco 3D, unión panorámica y enlace con radar. Alojada en aleación de aluminio integral con protección IP66 (IP67 opcional), opera desde -25°C hasta +60°C e incluye resistencia a sobretensiones, vibración y niebla salina para entornos exteriores adversos.

RESUMEN

- Detector VOx no refrigerado 640×512
- NETD inferior a 50mK (@25°C F1.0)
- Procesamiento de imagen digital SDE, AGC, amplificación digital 2X
- 10 pseudocolores y B/N, inverso B/N
- Funciones inteligentes: detección transfronteriza/de intrusión y seguimiento de objetivos
- Umbral de alarma de 255 niveles configurable
- Algoritmo avanzado que admite detección y alerta de punto de disparo/incendio
- Alojamiento integral de una sola pieza de aleación de aluminio, impermeable, resistente a la intemperie IP66, antipolvo

APLICACIONES

- Vigilancia de puertos marítimos y aeropuertos
- Vigilancia de sistemas de agua
- Vigilancia de almacenamiento
- Seguridad de campos petrolíferos y depósitos de petróleo
- Monitoreo ecológico y ambiental
- Defensa fronteriza y costera
- Vigilancia de carreteras y ferrocarriles

ESPECIFICACIONES TÉCNICAS

THERMAL	
Field of View	30°* 23°~6.2°*4.6°
Zoom	Electric zoom
Focus	manual / auto focus, 3A adaptive active focus algorithm, support multiple trigger modes, precise high speed
Optical Machine	3CAM mode and AS+DOE optical machine structure, high infrared transmittance, no virtual focus and small axis in the zoom process
Image Enhancement	SDE digital image enhancement technology to enhance image details
Pseudo-color / Polarity	16 kinds of pseudo-color images, hot black / hot white two polarities
Image Parameters	AGC automatic gain control, brightness, contrast
Electronic Zoom	2X, 4X, support global synchronous display
NUC Correction	automatic / manual correction, background correction
VISIBLE	
Sensor Type	1/2.8" target surface star-level CMOS, integrated ICR dual filter day and night switching
Resolution	2 Mega pixels, 1920X1080
Min Illumination (Color)	0.05 Lux
Min Illumination (B/W)	0.01 Lux
Encoding	H.265/H.264 video format, support multi-stream
Video Bit Rate	32Kbps ~ 16Mbps
Frame Rate	60Hz 30 frames / sec
Local Storage	SD card local storage
Motion Detection	support

ESPECIFICACIONES TÉCNICAS

VISIBLE	
Occlusion Alarm	support
Cross-border Detection	support
Regional Intrusion Detection	support
White Balance	support
Electronic Shutter	support
Strong Light Suppression	support
3D Digital Noise Reduction	support
Wide Dynamic	support
Anti-infrared Over Exposure	support
Lens Focal Length	8 ~ 320mm, 2 Mega pixel high-definition power zoom
Lens Focus	manual / auto focus, 3A adaptive active focus algorithm, support multiple trigger modes, precise high speed
Aperture	Automatic
Day/Night Type Light	0.4-0.75um visible light wide spectral window and 0.8-0.95um near infrared laser narrow spectrum window day and night independent double pass light window to improve imaging light and stray light signal to noise ratio
Preset Position	precision potentiometer, zoom focus feedback
LASER	
Availability	optional
Power	8W
Wavelength	810nm infrared laser
Illumination Angle	1°~ 20°, DSS digital step lighting angle control technology

ESPECIFICACIONES TÉCNICAS

LASER	
Homogenization	GHT-II high-definition lens group ultra-homogenization patented technology, brightness balance of all focal lengths is >92%
Laser Safety	ZQB safety laser beam processing patent technology, in line with international IEC60825 safety standards
HOUSING	
Material	integral aluminum alloy housing, stainless steel, anti strong wind
Structure	Integral double window
Window Glass	4mm optical glass, transmission>98%
Surface Coating	PTA three-proofing coatings
IP Rating	IP66 (IP67 optional)
Thermal Balance Design	applied thermal balance design and wide temperature electronics, which could operate under high / low temperature
Connector	waterproof aviation connector
PTZ	
Load	50kg
Pan Range	0 ~ 360°
Tilt Range	-45°~ +45°
Horizontal Speed	0.01°/S ~ 30°/S
Pitch Speed	0.01°/S ~ 15°/S
Speed Adaptive	support lens focal length speed adaptive function
Preset Positions	255, support lens zoom, focus preset
Accuracy	±0.1°
Patrol Sweep	support 6 cruises, 1 apple peel, 1 line sweep

ESPECIFICACIONES TÉCNICAS

PTZ	
Watch	Preset / Auto Cruise Route / Auto Scan Route
Power-off Memory	support (recoverable position before power-off, preset position status, cruise status, line sweep status)
Bearing Information	support angle query return, positioning
Zero Point Correction	support north direction zero point remote correction function
Power Consumption	about 100W
Weight	15kg
INTERFACE	
Network Interface	1 way RJ45, 10/100 Base-T adaptive (integrated video output and RS422/485 control communication)
Network Protocol	support TCP/IP, UDP, IPv4/v6; support HTTP, RTP, RTSP, NFS, DHCP, NTP, SMTP, SNMPv1/v2c/v3, UPNP, PPPoE, DNS, FTP; support PSIA, ONVIF2.0, GB28181 and other network protocols
Physical Interface	alloy waterproof aviation plug
POWER	
Power Supply	AC/DC24V, anti-reverse protection
Total Power Consumption	150W
WEIGHT	
Total Weight	35kg (including Pan/Tilt)
ENVIRONMENT	
Working Temperature	-25°C~ +60°C (optional -40°C)
Storage Temperature	-45°C~ +70°C
Humidity	<90%
Earthquake Resistance	0.2g (according to the 5.4 severity level 2 of GB/T15211-2013)
Impact Resistance	15g (according to the 5.3 severe level 3 of GB/T15211-2013)
Lightning Protection	built-in surge protection of interface circuit, power supply 4000V, signal 2000V

ESPECIFICACIONES TÉCNICAS

ENVIRONMENT	
Anti-salt Fog	at pH 6.5 ~ 7.2, continuous spraying for 96 hours, no change in surface
ENHANCEMENTS	
Glare Protection	support, anti-sun burn function
Temperature Correction	no thermal image design, imaging resolution is not affected by temperature
Scene Mode	support multiple configuration scenarios, adapt to various environment applications
Auto Focus Tuning	support remote auto focus precision parameter adjustment, adapt to different scenes
Day/Night Cruise	day and night group cruise different preset groups, day cruise 1-40 preset position, night cruise 41-80 preset position, automatically switch day and night according to the photosensitive state, adapt to different time and space scenes
Lens Servo	support lens preset position, focal length return, focus positioning function
OSD Menu	OSD menu remote call operation
Remote Maintenance	support embedded program remote upgrade for easy after-sales maintenance
Alarm Threshold	255 level alarm threshold can be setup
Fire Detection	support shot-point / fire detection and alert
OPTIONS	
Wiper	optional built-in wiper
Window Cleaning	optional external small spray device, self-storing water, no damage to ice, no impact on host function
Expansion Module	optional Beidou / GPS, laser ranging and other extended functions
Optical Network	optional built-in fiber module, single-mode fiber output, improve anti-interference
INTELLIGENT FUNCTIONS	
Regional Intrusion Detection	support
Cross-border Intrusion Detection	support
Multi-scene Group Cruise Detection	support

ESPECIFICACIONES TÉCNICAS

INTELLIGENT FUNCTIONS

3D Frame Selection Zoom / Positioning	support
Automatic Tracking	support
Panoramic Stitching	support
Radar Linkage	support (requires key area prevention software)

HOJA DE CONTROL DEL DOCUMENTO

AUTORIDAD EMISORA	
ORGANIZACIÓN	Volls Global Inc
DOMICILIO SOCIAL	1207 Delaware Ave #5352
LOCALIDAD	Wilmington, DE 19806
PAÍS	Estados Unidos
PUNTO DE CONTACTO	info@circuitbull.com
MARCA	Circuitbull®
ORGANIZACIÓN MATRIZ	Volls Global · volls.us

CÓDIGOS DE MATRIZ · ESCANEAR PARA ABRIR			
01	02	03	04
			
ESTE PRODUCTO circuitbull.com/.../ agt-htvc6511-2132-49262612	DOMICILIO REGISTRADO 1207 Delaware Ave #5352	SITIO PRINCIPAL circuitbull.com	VOLLS GLOBAL volls.us

DECLARACIÓN DE DISTRIBUCIÓN
No controlado una vez impreso. Verifique la revisión vigente en la dirección del producto antes de la adquisición o el uso. Esta hoja identifica a la organización emisora y las direcciones digitales de este documento.