



CATÁLOGO DE MISIÓN · CB-000035

AGT-TC6519 IR HIGH SPEED THERMAL IMAGING CAMERA FOR BUILDING INSPECTION

Vigilancia térmica de largo alcance, día y noche, en cualquier condición climática.

Modelo AGT-TC6519

BENEFICIOS CLAVE

- Long range 24-hours monitoring
- Delicate and smooth images
- Convenient for installation and application
- 360 degree omni-directional Pan-Tilt
- Super-strong aluminum alloy with IP66
- Higher sensitivity
- Effective in all environments
- Small size and low weight

DESCRIPCIÓN

La AGT-TC6519 es una cámara térmica PTZ de alta velocidad y largo alcance diseñada para la inspección de edificios y la vigilancia crítica de infraestructuras. Integra un detector VOx no refrigerado de 640×512 píxeles con zoom continuo motorizado de 38–190mm, procesamiento digital SDE, AGC y amplificación digital 2× para ofrecer imágenes térmicas nítidas y estables durante el día, la noche y condiciones meteorológicas adversas. Su PTZ CNC de alta precisión permite paneo de 360°, inclinación de $\pm 45^\circ$ y velocidades de hasta 60°/s, mientras que sus funciones inteligentes —detección de intrusión, seguimiento de objetivos y alerta de fuego— la convierten en una solución robusta para puertos, aeropuertos, fronteras, bases militares, oleoductos y aplicaciones antidrones. Con protección IP66 en aleación de aluminio de una sola pieza, garantiza un rendimiento fiable las 24 horas.

RESUMEN

- VOx uncooled detector, 640×512 (384×288 optional)
- NETD less than 50mK (@25°C F1.0)
- SDE digital image processing, AGC, 2X digital amplification
- 10 pseudo color and B/W, B/W inverse
- Intelligent functions: cross-border/intrusion detection and target tracking
- 255 level alarm threshold can be setup
- Advanced algorithm support shot-point/fire detection and alert
- One integral aluminum alloy housing, waterproof, IP66 weatherproof, anti-dust

APLICACIONES

- Seaport and airport monitoring
- Water system monitoring
- Storage monitoring
- Base security monitoring
- Oilfield & oil depot security
- Fire source prevention & monitoring
- Ecological and environmental monitoring
- Border and coastal defense
- Urban security and anti-UAV applications
- Highways and railways monitoring

ESPECIFICACIONES TÉCNICAS

OPTICAL	
Field of view	17.6°x13.2° - 3.5°x2.6°
DETECTION	
Vehicle range	16400m
Human range	5800m
IDENTIFICATION	
Vehicle range	4200m
Human range	1600m
PTZ	
Duty	30kg CNC PT
Pan range	0~360°
Tilt range	-45°~+45°
Pan speed	0.01°~60°/S
Tilt speed	0.01°/S ~30°/S
Accuracy	±0.1°
Presets	255
Preset features	lens zooming and focusing preset
Cruising lines	6
Apple-skin scanning	1
Line-cruising	1
INTERFACE	
Interface type	RJ45.10
Network speed	10/100 Base-T adaptive

ESPECIFICACIONES TÉCNICAS

INTERFACE	
Integrated video output	RS422/485
NETWORK	
Transport protocols	TCP/IP, UDP, IPv4/v6
Application protocols	HTTP, RTP, RTSP, NFS, DHCP, NTP, SMTP, SNMPv1/v2c/v3, UPNP, PPPoE, DNS, FTP
Standards / compliance	PSIA, ONVIF2.0, GB28181
ENVIRONMENT	
Operating temperature	-25°C~+60°C (-40°C optional)
Storage temperature	-45°C~70°C
Protection level	IP66
POWER	
Power supply	AC/DC24V
Protection	anti-reverse connection protection
CONSUMPTION	
Total consumption	180W
WEIGHT	
Total weight	≤25kg (include PTZ)
ENHANCEMENTS	
Image processing	SDE digital image processing
AGC	Supported
Digital amplification	2X
Pseudo color count	10
Monochrome	B/W
Monochrome inverse	B/W inverse
Cross-border detection	Supported

ESPECIFICACIONES TÉCNICAS

ENHANCEMENTS	
Intrusion detection	Supported
Target tracking	Supported
Alarm threshold levels	255
Shot-point detection	Supported
Fire detection	Supported
Monitoring capability	Long range 24-hours monitoring
Image quality	Delicate and smooth images
Installation	Convenient for installation and application
Environmental effectiveness	Effective in all environments
APPLICATIONS	
Seaport and airport monitoring	Supported
Water system monitoring	Supported
Storage monitoring	Supported
China base security monitoring	Supported
Oilfield & oil depot security	Supported
Fire source prevention & monitoring	Supported
Ecological and environmental monitoring	Supported
Border and coastal defense	Supported
Urban security and anti-UAV applications	Supported

ESPECIFICACIONES TÉCNICAS

APPLICATIONS

Highways and railways monitoring

Supported

HOJA DE CONTROL DEL DOCUMENTO

AUTORIDAD EMISORA	
ORGANIZACIÓN	Volls Global Inc
DOMICILIO SOCIAL	1207 Delaware Ave #5352
LOCALIDAD	Wilmington, DE 19806
PAÍS	Estados Unidos
PUNTO DE CONTACTO	info@circuitbull.com
MARCA	Circuitbull®
ORGANIZACIÓN MATRIZ	Volls Global · volls.us

CÓDIGOS DE MATRIZ · ESCANEAR PARA ABRIR			
01	02	03	04
			
ESTE PRODUCTO circuitbull.com/.../ agt-tc6519-48441712	DOMICILIO REGISTRADO 1207 Delaware Ave #5352	SITIO PRINCIPAL circuitbull.com	VOLLS GLOBAL volls.us

DECLARACIÓN DE DISTRIBUCIÓN
No controlado una vez impreso. Verifique la revisión vigente en la dirección del producto antes de la adquisición o el uso. Esta hoja identifica a la organización emisora y las direcciones digitales de este documento.