



GÖREV KATALOĞU · CB-000005

AGT-TC6516 LONG RANGE PROFESSIONAL THERMAL IMAGING CAMERA FOR FIREFIGHTING

13 km'ye kadar araç tespiti; 360° PTZ ve IP66 gövdeyle kesintisiz 7/24 termal güvenlik.

Model AGT-TC6516

TEMEL FAYDALAR

- Long range 24-hours monitoring
- Delicate and smooth images
- Convenient for installation and application
- 360 degree omni-directional Pan-Tilt
- Super-strong aluminum alloy with IP66
- Higher sensitivity
- Effective in all environments
- Small size and low weight

AÇIKLAMA

AGT-TC6516, itfaiye, sınır güvenliği ve kritik altyapı uygulamaları için tasarlanmış uzun menzilli profesyonel bir termal görüntüleme kamerasıdır. Beşinci nesil FPA VOx soğutmasız dedektör, 640×512 çözünürlük (isteğe bağlı 384×288), 31–155mm sürekli zoom lens ve gelişmiş SDE dijital görüntü işleme teknolojisi sayesinde her koşulda detaylı ve akıcı termal görüntüler sunar. 30 kg taşıma kapasiteli CNC PTZ başlık, 360° yatay ve $\pm 45^\circ$ dikey hareket ile $\pm 0,1^\circ$ hassasiyet sağlarken 255 ön ayar ve çoklu turlama modu ile otomatik bölge kapsamı yapar. Entegre akıllı video analizleri; sınır ihlali, izinsiz giriş, hedef takibi, ateş/ısı kaynağı tespiti ve 255 seviyeye kadar ayarlanabilir alarm eşiği sunar. Tek parça süper güçlü alüminyum alaşım gövde, IP66 hava koşullarına dayanıklılık ve toz koruması ile -25°C ila +60°C arasında güvenilir 7/24 çalışma sağlar.

GENEL BAKIŞ

- VOx uncooled detector, 640×512 (384×288 optional)
- NETD less than 50mK (@25°C F1.0)
- SDE digital image processing, AGC, 2X digital amplification
- 10 pseudo color and B/W, B/W inverse
- Intelligent functions: cross-border/intrusion detection and target tracking
- 255 level alarm threshold can be setup
- Advanced algorithm supports shot-point/fire detection and alert
- One integral aluminum alloy housing, waterproof, IP66 weatherproof, anti-dust

UYGULAMALAR

- Seaport and airport monitoring
- Water system monitoring
- Storage monitoring
- Base security monitoring
- Oilfield & oil depot security
- Fire source prevention & monitoring
- Ecological and environmental monitoring
- Border and coastal defense
- Urban security and anti-UAV applications
- Highways and railways monitoring

TEKNİK ÖZELLİKLER

DETECTION	
Vehicle range	13000m
Human range	4800m
IDENTIFICATION	
Vehicle range	3400m
Human range	1300m
PTZ	
Duty	30kg CNC PT
Pan range	0~360°
Tilt range	-45°~+45°
Pan speed	0.01°~60°/S
Tilt speed	0.01°/S ~30°/S
Accuracy	±0.1°
Presets	255
Preset lens support	support lens zooming and focusing preset
Cruising lines	6
Apple-skin scanning	1
Line cruising	1
NETWORK	
Network interface	RJ45.10, 10/100 Base-T adaptive
Video output	RS422/485 integrated
Transport protocols	TCP/IP, UDP, IPv4/v6

TEKNİK ÖZELLİKLER

NETWORK	
Application protocols	HTTP, RTP, RTSP, NFS, DHCP, NTP, SMTP, SNMPv1/v2c/v3, UPNP, PPPoE, DNS, FTP
Standards	PSIA, ONVIF2.0, GB28181
POWER	
Input voltage	AC/DC24V
Reverse polarity protection	anti-reverse connection protection
CONSUMPTION	
Total consumption	180W
WEIGHT	
Weight	≤25kg (include PTZ)
ENVIRONMENT	
Operating temperature	-25°C~+60°C(-40°C Optional)
Storage temperature	-45°C~70°C
Protection level	IP66
ENHANCEMENTS	
Image processing	SDE digital image processing
AGC	supported
Digital amplification	2X
Pseudo color count	10
Monochrome modes	B/W, B/W inverse
Cross-border detection	supported
Intrusion detection	supported
Target tracking	supported
Alarm threshold levels	255

TEKNİK ÖZELLİKLER

ENHANCEMENTS

Shot-point detection	supported
Fire detection	supported
Alert	supported

TİCARİ TEKNİK VERİ

VERİ SAYFASI · TR

BELGE KONTROL SAYFASI

DÜZENLEYEN MAKAM

KURULUŞ	Volls Global Inc
KAYITLI ADRES	1207 Delaware Ave #5352
YERLEŞİM	Wilmington, DE 19806
ÜLKE	Amerika Birleşik Devletleri
İRTİBAT NOKTASI	info@circuitbull.com
MARKA	Circuitbull®
ANA KURULUŞ	Volls Global · vols.us

MATRİS KODLARI · OKUTARAK AÇIN

01	02	03	04
			
BU ÜRÜN circuitbull.com/.../ agt-tc6516-40541712	KAYITLI ADRES 1207 Delaware Ave #5352	ANA SİTE circuitbull.com	VOLLS GLOBAL volls.us

DAĞITIM BİLDİRİMİ

Basıldığında kontrolsüz kopyadır. Tedarik veya kullanımdan önce güncel revizyonu ürün adresinden doğrulayın. Bu sayfa, düzenleyen kuruluşu ve bu belgenin sayısal adreslerini tanımlar.